

# Barber M-976 AAR Spring Groups

	S-2-D	S-2-D	S-2-HD	S-2-HD-9C	S-2-E	S-2-E*
Spring Travel	3 11/16	3 11/16	3 11/16	3 11/16	3 11/16	3 11/16
Solid Height	6 9/16	6 9/16	6 9/16	6 9/16	6 9/16	6 9/16
Wedge	907-SW	935-SW	915-SW	915-SW	917-C	945-SW
Bearing Adapter and Shear Pad	AAR Standard Adapter with 5578 Shear Pad	AAR Standard Adapter with 5578 Pad	AAR Standard Adapter with 5578 Pad	AAR Standard Adapter with 5578 Pad	AAR Standard Adapter with 5578 Pad	AAR Standard Adapter with 5578 Pad
	6366 Bearing Adapter with 6367 Shear Pad (S2-86 Radial Adapter)	6366 Bearing Adapter with 6367 Shear Pad (S2-86 Radial Adapter)	6366 Bearing Adapter with 6367 Shear Pad (S2-86 Radial Adapter)	6366 Bearing Adapter with 6367 Shear Pad (S2-86 Radial Adapter)	6366 Bearing Adapter with 6367 Shear Pad (S2-86 Radial Adapter)	6366 Bearing Adapter with 6367 Shear Pad (S2-86 Radial Adapter)
6 1/2 x 9 Bearing Size						
286,000 LBS. Max Rail Load	7 Outers D5 4 Inners D5 2 Outer Sides B-701 2 Inner Sides B-702 2 Third Sides D6A	7 Outers D5 4 Inners D5 2 Outer Sides B-701 2 Inner Sides B-702 2 Third Sides D6A	6 Outers D5 7 Inners D6 4 Third Loads D6A 2 Outer Sides B-353 2 Inner Sides B-354	7 Outers D5 7 Inners D5 2 Outer Sides B-353 2 Inner Sides B-354	7 Outers D5 5 Inners D5 2 Outer Sides B-360 2 Inner Sides B-361 2 Third Sides D6A	7 Outers D5 7 Inners D5 2 Outer Sides B-353 2 Inner Sides B-354
Solid Capacity (LBS.)	97,891	97,891	105,605	105,570	98,538	105,570

- Approved S-286 truck system for Open Top Cars with C.G. less than 95 inches, and Covered Hopper Cars with 45'-9" truck centers and C.G. less than 95 1/2 inches.

- Outer
- Inner
- Third

Always Use Original  
Barber Parts



Wabtec, Standard Car Truck

6400 Shafer Court – Ste 450, Rosemont, Illinois 60018, U.S.A.  
Telephone: 847-692-6050 Fax: 847-692-6299

Not A  
Controlled  
Document